

*Movable X-ray generator series
Multi-setup
150mA - 300mA - 500mA / 125Kvp*

FEATURES

Soft touch selection system (Membrane keypad), on/off power, with bucky/without bucky, time selection, technique selection, readiness, rays and blockage indicators.

Source voltage, kilovoltage and exposure time in LCD display.

«Wireless» remote control trigger for distance.

Low frequency and high voltage generator holding one tube winded over a iron shielded nucleus, siliceous grain oriented, complete monofasic rectified wave with solid state silicon rectifiers, the whole set closed in dielectric oil.

TECHNICAL DATA

OUTPUT	150mA @ 125 Kvp	300mA @ 125 Kvp	500mA @ 125Kvp
OUTPUT VOLTAGE	40 ~ 125Kvp	40 ~ 125Kvp	40 ~ 125Kvp
	10 ~ 10kV steps K.G 2 ~ 2kV steps K.F		
TUBE CURRENT	50mA - S.F 100, 150mA - L.F	50, 100mA - S.F 150, 200, 300mA- L.F	50, 100mA - S.F 150, 200, 300, 500mA -L.F
EXPOSURE TIME	Microprocessor controlled timer 0,02 ~ 3,5 secs. (25 steps)		
POWER RATINGS	220 / 380V ~ 15KW	220 / 380V ~ 30KW	220 /380V ~ 40KW



Ingeray S.R.L.

CAMPILLO 2585 (1427)

BUENOS AIRES - ARGENTINA

TE. (54 11) 45 23-39 99

(54 11) 45 23-57 92

TE./FAX (54 11) 45 23-57 92

www.ingeray.com.ar

e-mail: ventas@ingeray.com.ar

DISTRIBUTOR